



Model: SR40-334
 Type: SP4T w/Driver
 Termination: Reflective
 Frequency: 2.0-18.0 GHz
 Isolation: 80 dB
 Speed: 25 nS
 Size: 1.25" Octagon X 0.88"
 (<http://customwave.com/wp-content/uploads/2013/09/SR40-334.jpg>)



Model: CMCS0463
 Type: SPST w/Driver
 Termination: Non-Reflective
 Frequency: 0.5-6.0 GHz
 Isolation: 60 dB
 Speed: 12 nS
 Size: 1.0" X 1.0" X 0.53"
 (http://customwave.com/wp-content/uploads/2013/09/CMCS0463_1.jpg)



Model: SR20-314
 Type: SP2T
 Termination: Reflective
 Frequency: 0.1-20.0 GHz
 Isolation: 80 dB
 Speed: 1 μS
 Size: 1.5" X 1.0" X 0.3"
 (http://customwave.com/wp-content/uploads/2013/09/SR20-314_1.jpg)



Model: SN40-314
 Type: SP4T w/Driver
 Termination: Non-Reflective
 Frequency: 0.1-20.0 GHz
 Isolation: 80 dB
 Speed: 1 μS
 Size: 1.25" Octagon X 0.88"
 (<http://customwave.com/wp-content/uploads/2013/09/SN40-314-VP.jpg>)



Model: CMCS0337
 Type: SPST w/Driver
 Termination: Reflective
 Frequency: 2-18 GHz
 Isolation: 50 dB
 Speed: 12 nS
 Size: 1.0" X 0.9" X 0.5"
 (http://customwave.com/wp-content/uploads/2013/09/CMCS0337_1.jpg)



Model: SN20-314
 Type: SP2T w/Driver
 Termination: Non-Reflective
 Frequency: 0.1-20.0 GHz
 Isolation: 80 dB
 Speed: 1 μS
 Size: 1.5" X 1.0" X 0.3"
 (http://customwave.com/wp-content/uploads/2013/09/SN20-314_1.jpg)



Model: SR40-314
 Type: SP4T w/Driver
 Termination: Reflective
 Frequency: 2-18 GHz
 Isolation: 80 dB
 Speed: 1 μS
 Size: 1.25" Octagon X 0.88"
 (<http://customwave.com/wp-content/uploads/2013/09/SR40-314-VP.jpg>)



Model: CMCS0947A-C2
 Type: SPST w/Driver
 Termination: Non-Reflective
 Frequency: 0.1-12.0 GHz
 Isolation: 55 dB
 Speed: 3.0 nS
 Size: 1.0" X 0.9" X 0.53"
 (http://customwave.com/wp-content/uploads/2013/09/CMCS0947A-C2_thumb.jpg)



Model: SR20-334
 Type: SP2T w/Driver
 Termination: Reflective
 Frequency: 2.0-18.0 GHz
 Isolation: 80 dB
 Speed: 25 nS
 Size: 1.5" X 1.0" X 0.3"
 (http://customwave.com/wp-content/uploads/2013/09/SR20-334_1.jpg)